

- 15" 1024×768 high resolution Aspect ratio: 4:3
- Touch panel: 5-wire resistive
- High contrast: 1500:1
  High brightness: 300cd/m²
- Viewing angle: 170° / 170° (H/V)
- HDMI, VGA, DVI & A/V inputs Metal housing designIntegrated bracket for easy installation
- VESA & rear mounting methods






## **Applications**

- KIOSK / POS machine Transportation machine Ticketing machine Financial ATM Entertainment / Gaming machine HMlequipment controller monitor Public communication machine Public advertisement machine











	Panel	15" LED backlit
DISPLAY	Physical Resolution	1024×768
	Touch Panel	5-wire resistive
	Aspect Ratio	4:3
	Brightness	300cd/m²
	Contrast	1500:1
INPUT	Viewing Angle	170°/170° (H/V)
	HDMI	1
	DVI	1
	VGA	1
	USB	1 (for touch function)
	Audio (BNC)	1
POWER	Video (BNC)	1
	Current	1200mA
	Input Voltage	DC 12V
	Power Consumption	≤15W
	Operating Temperature	-20°C ~ 60°C
DIMENSION	Storage Temperature	-30°C ~ 70°C
	Mounting Method	VESA 75mm / 100mm, rear mount
	Dimension(LWD)	402×289×45.5mm / 400×279×43.5mm (open frame)
	Weight	3.2kg / 2.8kg (without touch panel)



Quanzhou Neway Industrial Limited

No. C-3 Xunmei Industrial Area Fengze, Quanzhou Fujian 362000 China Email: fb@newayil.com/sales@newayil.com Tel: +86-595-22519926